

AQUA 50

HYDROGEN PEROXIDE BASED DRINKING WATER TREATMENT

Kilco Aqua 50 is a highly effective oxidising water treatment based on Hydrogen Peroxide. Can be widely used for Agricultural biosecurity applications also in Aquaculture and the Dairy Industry.

- Effective removal of biofilm.
- Readily biodegrades to harmless by-products.
- Removes organic deposits.



RECOMMENDED USAGE

Animals present:	Maintenance dosing of water lines Under advice from your local Kilco representative dose Aqua 50 between 0.005% - 0.02% $(25ppm - 100ppm H_2O_2)$ from the original container via a metering pump suitable for dosing H_2O_2 . Alternatively, make up a stock tank solution at between 0.5% - 2% and further dilute into drinking water line via a fixed 1% volumetric dosing unit to give a point of consumption dilution in the 25ppm to 100ppm H_2O_2 range.
	It is important to empty and replenish stock tank solutions on a regular basis and also to cover stock tank with a fitted lid to protect solution from environmental contamination.
	Withdraw dosing 24 hours prior to and 12 hours post live vaccine treatments.
Advice:	Consult with your local Kilco representative for specific application recommendations.
Test method:	Use Hydrogen peroxide test strips on a regular basis to check and monitor residual H_2O_2 at point-of-consumption.
Storage:	Store upright in original container in a cool, well ventilated area away from sources of ignition, alkalis, acids and oxidising substances.
Pack size:	10 litres.
Shelf life:	I Year from date of manufacture.

KILCO (INTERNATIONAL) LTD. BROOMHOUSES 2 INDUSTRIAL ESTATE OLD GLASGOW ROAD, LOCKERBIE. DG11 2SD Tel: +44 (0) 1576 205 480 Fax: +44 (0) 1576 205 483 Email: enquiries@kilco.co.uk